
DS SERIES

DS491LT5

49" Fanless High Brightness Digital Signage Display






SUNLIGHT VIEWABLE IMAGE




FANLESS



BUILT-IN MEDIA PLAYER



TRUECOLOR™ CALIBRATED



ULTRA-QUIET

	LCD Panel Size	48.5"
PANEL	Native Resolution	1920 x 1080
	Brightness	4000 nits
	Color Depth	10 bits
	Contrast Ratio	3000:1
	Response Time (Typ.)	8 ms
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
	Blackening Defect Free	Up to 110°C (230°F)

Power Supply Internal POWER Rated Voltage 100-240V ~ 50/60HZ Power Consumption (Typ./ Max.) 160 W / 230 W

	Bezel Width (T/B/L/R)	8.7 / 8.7 / 8.5 / 8.5 mm
MECHANICAL SPECS	Monitor Dimension (LxHxI	·
	Monitor Weight	19.6 kg
	VESA Mounting (LxH)	400 x 400 mm
	Language	English
FEATURE	Support SNMP (Up to V3.6	O) Yes
	Image Retention Protectio	n Yes
	Auto Orientation Sensor	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
	OSD Menu Rotation	Yes
INPUT	HDMI 2.1 (HDCP 2.3)	x2
	DisplayPort 1.2	x1
	USB 3.0	x1
	Micro SD slot	X
OUTPUT	Audio	x1
	RS-232	In x1
EXTERNAL CONTROL	RJ-45	x2 (LAN)
	ETK Port (Thermal)	X1
	ESK Port (IR, Ambient)	X
INTERNAL PLAYER	Operating Temperature	0°~ 45° C
	Storage Temperature	-20°~60° C
	Humidity	10% ~ 80% RH Non-condensing
	Operating System	Android 8.0.0
	Processor	Dual-core A73 and dual-core A53
	Clock Speed	1.5GHz
	Main Memory Interface	DDR4, 2G
	Graphics	Quad-core MaliG51
	Wi-Fi Specification	802.11 b/g/n
ACCESSORY	Quick Start Guide. Power Cord. Remote Control. Batteries. IR & Ambient Sensor	
CERTIFICATION	CE / FCC / RoHS / PSE / Y	VCCI

CERTIFICATION CE / FCC / RoHS / PSE / VCCI

Android is a trademark of Google LLC.

The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

FOR MORE INFOMATION

