# DK SERIES DK651DR5

65" 4000 nits Dual-Sided Ultra-High Brightness Outdoor Kiosk





DUAL-SIDED DESIGN



SUNLIGHT VIEWABLE IMAGE



VANDAL RESISTANT



VIEWABLE WITH POLARIZED LENSES

WEATHER PROOF



### FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascandisplay.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.


# SPECIFICATION

MODEL		DK651DR5
DISPLAY	LCD Panel Size	65 inches LCD (x2)
	Native Resolution	1920 x 1080
	Brightness (w/o glass)	4,000 nits
	Color Depth	10 bits
	Contrast Ratio	4000 : 1
	Response Time (Typ.)	8 ms
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
	Blackening Defect Free	Up to 110°C (230°F)
	Polarized Sunglasses Support	Yes
	Detection method	Projected Capacitive Touch Technology
тоисн	Input method	Finger and gloved finger
(Optional)	Noise Shielding	Yes
	Number of simultaneous touche	Max. 40 points
POWER	Power Supply	Internal
	Rated Voltage	200-240V ~ 50/60Hz
	Power Consumption (Typ./ Max	<b>6</b> 50 W / 1800 W
	Bezel Width (T/B/L/R)	80.0 / 65.3 / 65.3 / 65.3 mm
	Cabinet Color	Black
	Kiosk Dimension (LxHxD)	2200.0 x 953.8 x 317.4 mm
MECHANICAL	Monitor Weight	380 kg
SPECS	Orientation	Portrait
	Glass	Double Laminated Tempered
	Air Vent	Top & Bottom
	Base	539.0 mm H
FEATURE	Language	English
	Image Retention Protection	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
INPUT	HDMI 2.1 (HDCP 2.3)	x6 (1080p recommended)
	DisplayPort	x2
	USB 3.0	x2
	Micro SD Slot	x2
OUTPUT	Audio	x2
EXTERNAL	RJ-45	x4 (LAN)
CONTROL		
	Operating Temperature	-30° C ~ 50° C
ENVIRONMENT	Storage Temperature	-20° C ~ 60° C
	Humidity	10% ~ 100% RH Non-condensing
	Water and Dust Resistant Desig	IP IP56
INTERNAL PLAYER	Operating System	Android 8.0.0
	Processor	Dual-core A73 and dual-core A53
	Clock Speed	1.5GHz
	Main Memory Interface	DDR4, 2G
	Graphics	Quad-core MaliG51
	Storage	Internal: 16GB eMMC Flash
PLATER	-	
PLATER	E	xternal: Support Micro SD ,Up to 32GB(exFAT) /128GB(FAT32)
PLATER	-	


CERTIFICATION CE/FCC/RoHS


### DIMENSIONS


Unit: mm [inch]











## DynaScan