


DK SERIES

DK861DR4


86" 3500 nits 4K UHD Dual-Sided Ultra-High Brightness Outdoor Kiosk



DUAL-SIDED
DESIGN



SUNLIGHT
VIEWABLE IMAGE



VANDAL
RESISTANT



VIEWABLE WITH
POLARIZED LENSES



WEATHER
PROOF

FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascandisplay.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.

DynaScan

SPECIFICATION

MODEL	DK861DR4	
DISPLAY	LCD Panel Size	85.6 inches LCD (x2)
	Native Resolution	3840 x 2160
	Brightness (w/o glass)	3,500 nits
	Color Depth	10 bits
	Contrast Ratio	3000 : 1
	Response Time (Typ.)	8 ms
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
	Blackening Defect Free	Up to 110°C (230°F)
	Polarized Sunglasses Support	Yes
POWER	Power Supply	Internal
	Rated Voltage	200-240V ~ 50/60Hz
	Power Consumption (Typ./ Max)	1500 W / 2700 W
MECHANICAL SPECS	Bezel Width (T/B/L/R)	95.2 / 106.7 / 134.4 / 134.4 mm
	Cabinet Color	Black
	Monitor Dimension (LxHxD, w/o stand)	2170.0 x 1338.0 x 254.0 mm
	Monitor Weight	500 kg
	Orientation	Portrait
	Glass	Double Laminated Tempered
	Air Vent	Top & Bottom
	Stand (Option)	58.0 mm H
FEATURE	Language	English
	Image Retention Protection	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
INPUT	HDMI 2.1 (HDCP 2.3)	x6 (2160p)
	DisplayPort 1.2	x2
	USB 3.0	x2
	Micro SD Slot	x2
OUTPUT	Audio	x2
EXTERNAL CONTROL	RS-232	In x2
	RJ-45	x4 (LAN)
ENVIRONMENT	Operating Temperature	-30° C ~ 50° C
	Storage Temperature	-20° C ~ 60° C
	Humidity	10% ~ 100% RH Non-condensing
	Water and Dust resistant design	IP56
CERTIFICATION	CE / FCC / IEC60950-22 / RoHS	

DIMENSIONS

Unit: mm [inch]

