



6мм BEZEL ULTRA LARGE TOUCHSCREEN

EASILY IMPLEMENT TOUCH VIDEO WALLS

TILE is an Ultra-Thin Bezel All-In-One 55" touch solution ready to quickly integrate and implement an interactive video wall. It combines great functionalities with great sleek design.

BEST WAY TO COLLABORATE

Make collaboration part of your day. Share moments and ideas with others on a canvas that is as big as your vision.

DESIGNED FOR MODERN WORKPLACES & EXPERIENCES

TILE integrates beautifully into the modern workplace, enabling productivity in any space where people come together to get things done. The fully integrated design, and flexible mounting configurations - LANDSCAPE, PORTRAIT and TABLE modes - makes this the best solution for your needs.



Recognizes up to 100 touch points per TILE with precision, allowing multiple people to interact with each screen simultaneously.



WORKS WITH ANY OS

TILE is based on SKIN ULTRA technology that runs on Windows, macOS, Android, Ubuntu and Chrome OS.



OBJECT RECOGNITION

It has great versatility as it can be used as a table with object recognition. You can have up to 6 TAGS simultaneously working on each touchscreen.

DESIGNED FOR MODERN WORKPLACES

SHOWROOMS, RETAIL, MEETING ROOMS





SIZE

55"

MOUNTING OPTIONS

- Rolling Stand
- Wall Mount
- Table

TOUCH PRE-CONFIGURED

We offer an easy set up and configuration so you can install several TILES quickly.

SOFTWARE TO CONTROL THE VIDEO WALL REMOTELY

- Color adjustment
- Video wall configuration and orientation
- Bezel correction
- Save Video wall configurations and load programmatic each one of them

SPECIFICATIONS





24/7

Operating Hours





For Videowalls with Pointer Events





© DISPLAX S.A., All rights reserved. This datasheet is for informational purposes only. DISPLAX makes no warranties, expressed or implied, with respect to the informat

TECHNICAL SPECIFICATIONS

DISPLAX TILE

GENERAL

•	
Detection Method	Projected Capacitive Technology Multitouch
Input Method Sizes	Finger and Gloved Finger
Diagonal Inches	55"
Aspect Ratio Glass	16:9
Substrate Glass	Extra Clear Anti-Fingerprint Coated Toughened Glass
Glass Thickness	3,3 mm
Bezel Color	Black Matte
Interface OS	HID
Multitouch Single Unit	Windows, Linux, Android, Chrome OS, Generic Media Players, others
Multitouch Videowall Mode	Windows 10 (Recommended)
OS Single Touch	Mac OS X Yosemite (Multitouch Support Through TUIO Bridge for Applications)
Data Connectivity	USB 2.0
LCD Bezel	6mm - Equal in all sides - Top, Bottom, Left, Right
LCD Weight	40,5 Kg
LCD Dimensions	1223 × 694 mm
Object Recognition	YES - Compatible with 6 TAGS
Touch Interactions	Pointer or Touch Events for Single Unit Pointer Events for Video Walls

DISPLAY

Panel Type	IPS / EDGE LED
Touch Response Time	5 milliseconds
Aspect Ratio	16:9
Contrast Ratio	1400:1
Viewing Angle	178° / 178°
Display Resolution	1920 × 1080
Daisy Chain	Up to 6 TILEs for each single Display Port Input
Brightness	500 cd/m ²
Panel Lifetime Color	Aprox. 60000 Hours
Depth	1.07 Billion Color
Panel Position	Landscape / Portrait / Table
VESA Mount	600×400
Power Consumption	190 W
Power	100 - 240 V AC


ENVIRONMENTAL		P	PACKAGE		
Operating Temperature	0° to 40° C	Bo	ox Dimensions	1450 × 890 × 280 mm	
Storage Temperature	-20° to 60° C	Bo	ox Weight	48,75 Kg	
Warranty	1 Year	C	Contains: TILE + Remote Control		
Support Details	support@displax.com	Co	Cables: 180cm Display Port, 160cm HDMI,		
	https://support.displax.com	18	180cm USB A/B, 180cm Power		


DISPLAX

TECHNICAL DRAWINGS

DISPLAX TILE







DISPLAX

This dataset is for informational purposes only. DISPLAX makes no warranties, expressed or implied, with respect to the information presented her

MKT.343.10